

EVIDEN

BullSequana Agility

BullSequana SA21Si

The BullSequana Agility family features a versatile range of 1- and 2-socket BullSequana SA servers, manufactured in France and powered by the latest generations of AMD EPYC™ and Intel® Xeon® Scalable processors. The servers are ideally suited for virtualized workloads and all modern architecture patterns, such as private and hybrid clouds, containerized infrastructures, hyper-converged and scale-out solutions. Various GPU options enable acceleration of AI/ML, video processing and image rendering workloads. BullSequana SA servers are delivered as standalone units or fully integrated in racks, along with networking and storage components to drastically reduce time to value.

The BullSequana SA21Si is the ultimate Intel® dual socket server for hyper-converged infrastructures hosting huge numbers of virtualized workloads. The 24 NVMe drives deliver outstanding IO capabilities, allowing the consolidation of large numbers of workloads in a dense 2U package.



Features

- Dual 4th Generation Intel® Xeon® Scalable processor
- 8-channel RDIMM DDR5 per processor, 32 x DIMMs
- Dual ROM technology supported
- 2 x 1Gb/s LAN port (Intel® I350-AM2)
- 1 x Dedicated management port
- 24 x 2.5" NVMe/SAS/SATA hot-swappable bays
- 4x2.5" SAS/SATA rear hot-swappable bays
- 4 x FHHL PCIe Gen5 expansion slots
- Dual 2000W 80 PLUS Titanium redundant power supply

Technical specifications

Dimensions	2U (W438 x H87.5 x D815 mm)
CPU	4 th Generation Intel® Xeon® Scalable processors Dual Intel® Xeon® Platinum, Gold or Silver processors CPU TDP up to 350W
Memory	32 x DIMM slots 8-channel DDR5 memory per processor RDIMM modules up to 128GB supported 3DS RDIMM modules up to 256GB* supported Memory speed: up to 4800 MT/s (1DPC), 4400 MT/s (2DPC)
LAN	2 x 1Gb/s LAN ports (1 x Intel® I350-AM2) Supported NCSI function 1 x 10/100/1000 management LAN
Video	Integrated in Aspeed® AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp,
Storage	12 x 2.5" NVMe/SATA/SAS hot-swappable bays 12 x 2.5" NVMe hot-swappable bays 4 x 2.5" SATA/SAS hot-swappable bays on rear side SAS card is required for SAS devices support
Expansion Slots	4 x PCIe Gen5 x16 FHHL slots

*256GB: check for availability with your sales representative

Front I/O	2 x USB 3.2 Gen1
Rear I/O	2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x RJ45, 1 x MLAN
Backpane I/O bandwidth	PCIe Gen4 x4 or SATA 6Gb/s or SAS 12Gb/s
TPM	1 x TPM header with SPI interface Optional TPM2.0 kit
Power supply	Dual 2000W (240V) 80 PLUS Titanium redundant power supply AC input: 100-240V
System fans	4 x 80x80x38 mm (18,300 rpm)
System management	Aspeed® AST2500 management controller Built-in html5 GUI iKVM RBAC, LDAP integration, RADIUS support SNMP, IPMI and Redfish management protocols SNMP trap, email and Redfish event notifications GSM server/ GSM agent for centralize monitoring of multiple BullSequana SA servers
Operating conditions	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
OS support	Windows Server 2019 / 2022 RHEL 9 VMware vSphere 8